

K4

LED Linear High Bay Light

IP54

SEVEN - YEAR



7

WARRANTY

175LM/W



VEET CB IK10




Product Description

- High luminous efficacy up to 175lm/w
- Separate heat sink for led driver and led chip
- Intelligent lighting: Zigbee wireless control, daylight sensor dimming, microwave sensor dimming, three in one(0-10v,PWM, resistance) dimming available
- Colorful housing can be customized



kWh/1000h



K4 LED Linear High Bay Light

Features

There is a junction box alongside the fixture for preventing wiring exposed outside. It is safer practice and complied with wiring code

Sandblasting oxidation treatment on heat sink makes fixture body with better abrasion performance and corrosion resistance



Aviation aluminum, customizable colors

The lenses are fixed by snap with less screws which makes assembling very conveniently.
With integral waterproof rubber around lens and rubber plug designed in outlet terminal, IP rating up to IP54
Three-dimensional diamond light guide technology

3030 SMD LED chip, high lumen
175LM/W



Accessories



Motion sensor



Daylight sensor




Zigbee wireless control



50W


SPECIFICATIONS



Technical Data

Model Number	HS-HB50W-K4
Power	50W
Luminous Efficacy	175lm/W
Lumen Output	8750lm
LED Quantity	84pcs
Dimension	305*110*54mm
CCT	3000K 4000K 5000K 6000K (Custom Option)
CRI	>80Ra
System Efficiency	≥90%
Beam angle	60°/90°/120°


Product Dimensions



Electrical Details

Input Voltage	AC100-277V/347V/480V
Power Frequency	50-60Hz
Output Voltage	DC36-48V
Power Efficiency	>92%
Power Factor	≥0.95
Total Harmonic Distortion	≤15%
Dimmable	Yes (Optional)

Photometrics



Other Details


IP Rating	IP54
Lifespan	100,000+ Hours
Storage Temperature	-20°~65°C
Operating Temperature	-20°~55°C
Luminaire Net Weight	1.4KG
Certification	UL,DLC Premium,SAA,TUV,VEET,CB
Color of housing	Blue+white(customized)

K4 LED Linear High Bay Light


SEVEN - YEAR

7


WARRANTY



Product Dimensions



Photometrics



100W

SPECIFICATIONS

Technical Data

Model Number	HS-HB100W-K4
Power	100W
Luminous Efficacy	175lm/W
Lumen Output	17500lm
LED Quantity	168pcs
Dimension	600*110*54mm
CCT	3000K 4000K 5000K 6000K (Custom Option)
CRI	>80Ra
System Efficiency	≥90%
Beam angle	60°/90°/120°

Electrical Details

Input Voltage	AC100-277V/347V/480V
Power Frequency	50-60Hz
Output Voltage	DC36-48V
Power Efficiency	>92%
Power Factor	≥0.95
Total Harmonic Distortion	≤15%
Dimmable	Yes (Optional)

Other Details


IP Rating	IP54
Lifespan	100,000+ Hours
Storage Temperature	-20°~65°C
Operating Temperature	-20°~55°C
Luminaire Net Weight	2.5KG
Certification	UL,DLC Premium,SAA,TUV,VEET,CB
Color of housing	Blue+white(customized)

K4 LED Linear High Bay Light

SEVEN - YEAR

7

WARRANTY




150W

SPECIFICATIONS


Technical Data

Model Number	HS-HB150W-K4
Power	150W
Luminous Efficacy	175lm/W
Lumen Output	26250lm
LED Quantity	252pcs
Dimension	895*110*54mm
CCT	3000K 4000K 5000K 6000K (Custom Option)
CRI	>80Ra
System Efficiency	≥90%
Beam angle	60°/90°/120°

Product Dimensions



Photometrics



Electrical Details

Input Voltage	AC100-277V/347V/480V
Power Frequency	50-60Hz
Output Voltage	DC36-48V
Power Efficiency	>92%
Power Factor	≥0.95
Total Harmonic Distortion	≤15%
Dimmable	Yes (Optional)


Other Details

IP Rating	IP54
Lifespan	100,000+ Hours
Storage Temperature	-20°~65°C
Operating Temperature	-20°~55°C
Luminaire Net Weight	3.2KG
Certification	UL,DLC Premium,SAA,TUV,VEET,CB
Color of housing	Blue+white(customized)




200W


SPECIFICATIONS



Product Dimensions



Photometrics



Technical Data

Model Number	HS-HB200W-K4
Power	200W
Luminous Efficacy	175lm/W
Lumen Output	35000lm
LED Quantity	336pcs
Dimension	1190*110*54mm
CCT	3000K 4000K 5000K 6000K (Custom Option)
CRI	>80Ra
System Efficiency	≥90%
Beam angle	60°/90°/120°

Electrical Details

Input Voltage	AC100-277V/347V/480V
Power Frequency	50-60Hz
Output Voltage	DC36-48V
Power Efficiency	>92%
Power Factor	≥0.95
Total Harmonic Distortion	≤15%
Dimmable	Yes (Optional)

Other Details

IP Rating	IP54
Lifespan	100,000+ Hours
Storage Temperature	-20°~65°C
Operating Temperature	-20°~55°C
Luminaire Net Weight	3.8KG
Certification	UL,DLC Premium,SAA,TUV,VEET,CB
Color of housing	Blue+white(customized)

K4 LED Linear High Bay Light


250W

SPECIFICATIONS


SEVEN - YEAR

7


WARRANTY



Product Dimensions



Photometrics



Technical Data

Model Number	HS-HB250W-K4
Power	250W
Luminous Efficacy	175lm/W
Lumen Output	43750lm
LED Quantity	336pcs
Dimension	1190*110*54mm
CCT	3000K 4000K 5000K 6000K (Custom Option)
CRI	>80Ra
System Efficiency	≥90%
Beam angle	60°/90°/120°


Electrical Details

Input Voltage	AC100-277V/347V/480V
Power Frequency	50-60Hz
Output Voltage	DC36-48V
Power Efficiency	>92%
Power Factor	≥0.95
Total Harmonic Distortion	≤15%
Dimmable	Yes (Optional)


Other Details

IP Rating	IP54
Lifespan	100,000+ Hours
Storage Temperature	-20°~65°C
Operating Temperature	-20°~55°C
Luminaire Net Weight	4.6KG
Certification	UL,DLC Premium,SAA,TUV,VEET,CB
Color of housing	Blue+white(customized)

Installation



Application



Widely use in Factory, Workshop, Warehouse, Logistics Center, Exhibition Hall, Stadium, Gas Station, Supermarket and etc.

Packing Info

Model No.	N.G(KG)	G.W (KG)	Pcs/carton	Carton Size(CM)
BA424	1.4	2.2	1	36*16*10.8
BA425	2.5	3.1	1	65.5*16*10.8
BA426	3.2	3.8	1	95*16*10.8
BA427	3.8	4.3	1	124.5*16*10.8
BA428	4.6	5.2	1	124.5*16*10.8